



Weatherproof outdoor network cables.

If you want to set up a network outside your home, you will find the right cable for different purposes in our outdoor network range. The most common applications are SOHO applications (small office, home office), connection of surveillance cameras, installation on building facades and connection to devices with RJ45 connection, such as game consoles, HDTV and printers, in the garden house or when camping. The cable sheaths are **resistant to weathering and UV radiation**.

For self-installation we have both **unassembled outdoor network cables** in different specifications, shielding classes and materials as well as two **CAT6 outdoor network cable sets** in two lengths each. The rolled goods can be extended and connected by dustproof and waterproof **outdoor LAN cable connectors** - completely without special tools and STP shielded and UTP unshielded as required.

Pre-assembled CAT6 outdoor network cables are available from a length of 10 metres. The patch cables can be quickly and easily extended and connected by using an outdoor RJ45 modular coupling via plug-and-play.

		Outdoor patch cable with RJ45 connectors		Outdoor network cable set	
Specification		CAT6			
Shielding class		U/UTP			
Material		Copper (Cu)	Copper-clad aluminium (CCA)	Copper (Cu)	Copper-clad aluminium (CCA)
Length	10 m	55432	94389		
	15 m	55433	94391		
	20 m	55434	94392		
	30 m	55435	94393		
	40 m	55436	94394		
	50 m	55437	94395		
	60 m	55438	94396		
	75 m	55439	94397		
	100 m			55440	94398
	305 m			55441	94399



Material cable sheath	PE
Cable sheath diameter (approx.)	6.6 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CU (copper)
AWG	24/1 (solid)
Shielding class	U/UTP
Connection, type	RJ45 male (8P8C)
Latch protection	both sides
Kink protection	both sides

Goobay

CAT 6 Outdoor-patch cable, U/UTP, black

copper material, PE-outer jacket

- unshielded LAN/network cable to connect network components with 2 RJ45 connectors
- UV- and water resistant
- double outer jacket (PE)
- with gold plated PINs
- with strain relief and latch protection
- suitable for 10/100/1000 Mbit-networks
- pair-sequence acc. to EIA/TIA 568B

10.00 m	55432	Bulk
15.00 m	55433	Bulk
20.00 m	55434	Bulk
30.00 m	55435	Bulk
40.00 m	55436	Bulk
50.00 m	55437	Bulk
60.00 m	55438	Bulk
75.00 m	55439	Bulk



Material cable sheath	PE
Cable sheath diameter (approx.)	6.2 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	24/1 (solid)
Shielding class	U/UTP
Connection, type	RJ45 male (8P8C)
Latch protection	both sides
Kink protection	both sides
Contacting	EIA/TIA-568B


Goobay

CAT 6 Outdoor-patch cable, U/UTP, black

CCA copper material mixture for SOHO application, PE-outer jacket

- unshielded LAN/network cable to connect network components with 2 RJ45 connectors
- UV- and water resistant
- double outer jacket (PE)
- with gold plated PINs
- with strain relief and latch protection
- suitable for 10/100/1000 Mbit-networks
- pair-sequence acc. to EIA/TIA 568B

10.00 m	94389	Bulk
15.00 m	94391	Bulk
20.00 m	94392	Bulk
30.00 m	94393	Bulk
40.00 m	94394	Bulk
50.00 m	94395	Bulk
60.00 m	94396	Bulk
75.00 m	94397	Bulk



Goobay

Outdoor (IP68) RJ45 modular connector, CAT 6

dustproof and waterproof, 2x RJ45 female (8P8C)

- IP68 dustproof and waterproof cable gland
- for outdoor/industrial applications
- offers increased protection for the connection against moisture and soiling
- quick and easy installation
- 2x shielded RJ45 port, assignment: 1:1
- for cable diameters of 4 - 8 mm
- suitable for PoE+ according to IEEE 802.3at

79566	Bulk
-------	------





Material cable sheath	PE
Cable sheath diameter (approx.)	6.6 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CU (copper)
AWG	24/1 (solid)
Shielding class	U/UTP

Goobay

CAT 6 Outdoor network cable set, U/UTP, black copper material, AWG 24/1 (solid), PE

- unassembled data/installation cable for processing and installation with LSA connection technology for home and outdoor use
- consists of: CAT 6 LAN cable, crimping tool, 100x cable ties and 100x RJ45 plugs
- unshielded twisted-pair LAN cable
- double-shielded
- resistant against UV and water damage
- suitable for gigabit (10/100/1,000 Mbit) network
- the cable included with delivery is not permitted for permanent installation in buildings.

100.00 m	55440	Bulk
305.00 m	55441	Bulk



Material cable sheath	PE
Cable sheath diameter (approx.)	6.8 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	24/1 (solid)
Shielding class	U/UTP

Goobay

CAT 6 outdoor network cable SET, U/UTP, black CCA copper mixture for SOHO applications, AWG 24/1 (solid), PE

- non-terminated data-/installation cable for processing and installation with LSA connection technology for Home-/outdoor usage
- box includes CAT 6 Lan cable, Crimp tool, pack of cable ties (100pcs) and pack of loose RJ45 plugs (100pcs)
- unshielded twisted-pair LAN cable
- double outer jacket, UV and water resistant
- suitable for Gigabit (10/100/1000 Mbit) network
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 70 m!
- This product is not approved for permanent installation in buildings.

100.00 m	94398	Bulk
305.00 m	94399	Bulk



Outdoor network cable (unassembled)									
Length		100 m							
Spezifikation		CAT7	CAT6				CAT5e		
Shielding class		S/FTP (PiMF)	S/FTP (PiMF)		U/UTP		SF/UTP	F/UTP	U/UTP
Material		Copper (Cu)	Copper (Cu)	Copper-clad aluminium (CCA)	Copper (Cu)	Copper-clad aluminium (CCA)	Copper-clad aluminium (CCA)		
AWG	26/7			57195				57295	57196
	24/7					57199			
	24/1		77624		77625		57296	57294	57198
	23/1	95419		57197		57293			



Material cable sheath	PE
Cable sheath diameter (approx.)	8.4 mm
max. bandwidth	600 MHz
Cable type	Cable type
Inner conductor material	CU (copper)
AWG	23/1 (solid)
Shielding class	S/FTP (PiMF)
Number of shieldings	2 x
Type 1, shielding	foil (alu) PiMF
Type 2, shielding	braid (aluminium)

Draka

CAT 7 outdoor installation cable, S/FTP (PiMF)

CU, AWG 23/1 (solid), PE

- non-terminated data-/installation cable for processing and installation with LSA connection technology for Home-/outdoor usage
- double shielded twisted-pair LAN cable
- LSOH/LSZH halogen free
- pairs screening: PiMF (pairs in metal foil) + outer shield: braiding
- This product is not approved for permanent installation in buildings.



100.00 m 95419 Cable Reel



Material cable sheath	PE
Cable sheath diameter (approx.)	6.3 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	26/7 (stranded)
Shielding class	S/FTP (PiMF)
Number of shieldings	2 x
Type 1, shielding	foil (alu) PiMF
Type 2, shielding	braid (aluminium) 64x

Goobay

CAT 6 outdoor network cable, S/FTP (PiMF), black

CCA copper mixture for SOHO applications, AWG 26/7 (stranded), PE

- non-terminated flexible data-/patch cable for Home-/outdoor usage
- double shielded twisted-pair LAN cable
- pairs screening: PiMF (pairs in metal foil) + outer shield: braiding
- This product is not approved for permanent installation in buildings.
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 40 m!



100.00 m 57195 Cable Reel



Material cable sheath	PE
Cable sheath diameter (approx.)	7.6 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CU (copper)
AWG	24/1 (solid)
Shielding class	S/FTP (PiMF)
Number of shieldings	2 x
Type 1, shielding	foil (alu) PiMF
Type 2, shielding	braid (aluminium) 64x

Goobay

CAT 6 outdoor network cable, S/FTP (PiMF), black

CU, AWG 24/1 (solid), PE

- non-terminated data-/installation cable for processing and installation with LSA connection technology for Home-/outdoor usage
- double shielded twisted-pair LAN cable
- pairs screening: PIMF (pairs in metal foil) + outer shield: braiding
- This product is not approved for permanent installation in buildings.

100.00 m 77624 Cable Reel



Material cable sheath	PE
Cable sheath diameter (approx.)	6.3 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	23/1 (solid)
Shielding class	S/FTP (PiMF)
Number of shieldings	2 x
Type 1, shielding	foil (alu) PiMF
Type 2, shielding	braid (aluminium) 64x


Goobay

CAT 6 outdoor network cable, S/FTP (PiMF), black

CCA copper mixture for SOHO applications, AWG 23/1 (solid), PE

- non-terminated data-/installation cable for processing and installation with LSA connection technology for Home-/outdoor usage
- double shielded twisted-pair LAN cable
- pairs screening: PIMF (pairs in metal foil) + outer shield: braiding
- This product is not approved for permanent installation in buildings.
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 70 m!

100.00 m 57197 Cable Reel



Material cable sheath	PE
Cable sheath diameter (approx.)	5.8 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	24/7 (stranded)
Shielding class	U/UTP

Goobay


CAT 6 outdoor network cable, U/UTP, black

CCA copper mixture for SOHO applications, AWG 24/7 (stranded), PE

- non-terminated flexible data-/patch cable for Home-/outdoor usage
- unshielded twisted-pair LAN cable
- This product is not approved for permanent installation in buildings.
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 40 m!

100.00 m 57199 Cable Reel





Material cable sheath	PE
Cable sheath diameter (approx.)	6.2 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CU (copper)
AWG	24/1 (solid)
Shielding class	U/UTP
Fire class (CPR) according to DIN EN 13501-6	F _{CA}



Goobay

CAT 6 outdoor network cable, U/UTP, black

CU, AWG 24/1 (solid), PE

- non-terminated data-/installation cable for processing and installation with LSA connection technology for Home-/outdoor usage
- unshielded twisted-pair LAN cable

100.00 m 77625 Cable Reel



Material cable sheath	PE
Cable sheath diameter (approx.)	5.8 mm
max. bandwidth	250 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	23/1 (solid)
Shielding class	U/UTP



Goobay

CAT 6 network cable, U/UTP, black

CCA copper mixture for SOHO applications, AWG 23/1 (solid), PE

- non-terminated data-/installation cable for processing and installation with LSA connection technology for Home-/outdoor usage
- unshielded twisted-pair LAN cable
- This product is not approved for permanent installation in buildings.
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 70 m!

100.00 m 57293 Cable Reel



Material cable sheath	PE
Cable sheath diameter (approx.)	5.6 mm
max. bandwidth	100 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	26/7 (stranded)
Shielding class	F/UTP
Number of shieldings	1 x
Type 1, shielding	foil (aluminium)

Goobay

CAT 5e outdoor network cable, F/UTP, black

CCA copper mixture for SOHO application, AWG 26/7 (stranded), PE

- non-terminated flexible data-/patch cable for Home-/outdoor usage
- UV and water resistant
- shielded twisted-pair LAN cable
- outer shield: foil screening
- This product is not approved for permanent installation in buildings.
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 40 m!

100.00 m 57295 Cable Reel





Material cable sheath	PE
Cable sheath diameter (approx.)	5 mm
max. bandwidth	100 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	26/7 (stranded)
Shielding class	U/UTP


Goobay

CAT 5e outdoor network cable, U/UTP, black

CCA copper mixture for SOHO applications, AWG 26/7 (stranded), PE

- non-terminated flexible data-/patch cable for Home-/outdoor usage
- UV and water resistant
- unshielded twisted-pair LAN cable
- This product is not approved for permanent installation in buildings.
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 40 m!

100.00 m 57196 Cable Reel



Material cable sheath	PE
Cable sheath diameter (approx.)	5.7 mm
max. bandwidth	100 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	24/1 (solid)
Shielding class	SF/UTP
Number of shieldings	2 x
Type 1, shielding	foil (aluminium)
Type 2, shielding	braid (aluminium)

Goobay

CAT 5e network cable, SF/UTP, black

CCA copper mixture for SOHO applications, AWG 24/1 (solid), PE

- non-terminated data-/installation cable for processing and installation with LSA connection technology for Home-/outdoor usage
- UV and water resistant
- double shielded twisted-pair LAN cable
- outer shield: braiding + foil screening
- This product is not approved for permanent installation in buildings.
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 70 m!

100.00 m 57296 Cable Reel



Material cable sheath	PE
Cable sheath diameter (approx.)	5.7 mm
max. bandwidth	100 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	24/1 (solid)
Shielding class	F/UTP
Number of shieldings	1 x
Type 1, shielding	foil (aluminium)

Goobay

CAT 5e outdoor network cable, F/UTP, black

CCA copper mixture for SOHO applications, AWG , PE

- non-terminated data-/installation cable for processing and installation with LSA connection technology for Home-/outdoor usage
- UV and water resistant
- shielded twisted-pair LAN cable
- outer shield: foil screening
- This product is not approved for permanent installation in buildings.
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 70 m!

100.00 m 57294 Cable Reel





Material cable sheath	PE
Cable sheath diameter (approx.)	5 mm
max. bandwidth	100 MHz
Cable type	Cable type
Inner conductor material	CCA (copper-clad aluminium)
AWG	24/1 (solid)
Shielding class	U/UTP

Goobay

CAT 5e outdoor network cable, U/UTP, black

CCA copper mixture for SOHO applications, AWG 24/1 (solid), PE

- non-terminated data-/installation cable for processing and installation with LSA connection technology for Home-/outdoor usage
- UV and water resistant
- unshielded twisted-pair LAN cable
- This product is not approved for permanent installation in buildings.
- Meets requirements for SOHO applications (Small Office, Home Office) up to a max. transmission length of 70 m!



100.00 m 57198 Cable Reel



44414



44416



Goobay

Outdoor (IP68) LAN cable connector


for IDC assembly, dust- and water resistant

- for easy connection of network installation cables - without special tools
- for outdoor / industrial applications - provides increased protection against dirt and moisture
- suitable for PoE+ according to IEEE 802.3at
- for conductor diameter solid wire 0.48 to 0.65 mm (AWG 22 to 26)
- or conductor diameter strand 7 * 0.16 to 7 * 0.20 mm (AWG 22 to 26)
- suitable for cable sheath diameters from 5.0 to 7.5 mm

CAT 6A shielded	44414	Bulk
CAT 6A UTP unshielded	44416	Bulk



44417



44415



CAT 6 shielded	44417	Bulk
CAT 6 UTP unshielded	44415	Bulk

