

2020

NEW Q2

Our product portfolio is constantly growing.

Discover exciting new products at a glance since the publication of the Wentronic product range.

CONTENT

TV & SAT

COAXIAL CABLES – INSTALLATION/REEL CABLES	2
---	---

AUDIO/VIDEO

HDMI – CABLE	3
--------------	---

DISPLAYPORT – CONNECTION CABLES	4
---------------------------------	---

TAB & PHONE

CHARGERS – FOR WALL SOCKETS	5
-----------------------------	---

BATTERIES

SPECIAL CELLS	6
---------------	---



2x geschirmt

Goobay

75 dB coaxial antenna cable, 2x shielded, 50 m, white

for digital Satellite- and CATV-cable systems, with copper/steel mixture inner conductor

- Suitable for receiving FULL HD 1080p
- double signal shield for sufficient protection over long distances

Shielding efficiency	75 dB
Cable type	coaxial cable
Inner conductor material	CCS
Number of shieldings	2 x
Type 1, shielding	foil (aluminium)
Type 2, shielding	braid (aluminium) 32x
Cable sheath diameter (approx.)	5 mm
Dielectric diameter	3.3 mm
Meter scaling	yes
inner conductor, core diameter	0.7 mm
Fire class (CPR) according to DIN EN 13501-6	E _{ca}

49759 Cable Reel



2x geschirmt

Goobay

90 dB coaxial antenna cable, 2x shielded, 25 m, white

for digital Satellite- and CATV-cable systems, with copper/steel mixture inner conductor

- Suitable for receiving FULL HD 1080p/ULTRA HD 4K
- double signal shield for sufficient protection over long distances

Shielding efficiency	90 dB
Cable type	coaxial cable
Inner conductor material	CCS
Number of shieldings	2 x
Type 1, shielding	foil (aluminium)
Type 2, shielding	braid (aluminium) 64x
Cable sheath diameter (approx.)	6.5 mm
Dielectric diameter	4.8 mm
Meter scaling	yes
inner conductor, core diameter	9 mm
Fire class (CPR) according to DIN EN 13501-6	E _{ca}

49760 Cable Reel



4x geschirmt

Goobay

120 dB coaxial antenna cable, 4x shielded, 20 m, white

for digital Satellite- and CATV-cable systems, with copper/steel mixture inner conductor

- Suitable for receiving FULL HD 1080p/ULTRA HD 4K
- quadruple signal shield for excellent protection over long distances

Shielding efficiency	120 dB
Cable type	coaxial cable
Inner conductor material	CCS
Number of shieldings	4 x
Type 1, shielding	foil (aluminium)
Type 2, shielding	braid (aluminium) 72x
Type 3, shielding	foil (aluminium)
Type 4, shielding	braid (aluminium) 64x
Cable sheath diameter (approx.)	7.2 mm
Dielectric diameter	4.55 mm
Meter scaling	yes
inner conductor, core diameter	1 mm
Fire class (CPR) according to DIN EN 13501-6	E _{ca}

49761 Cable Reel



New length!



Goobay Series 2.1 8K

Ultra High Speed HDMI™ Cable with Ethernet

High speed cable for 8K@60 Hz

- Ultra HD up to 8K@60Hz (4320p), 4K@120Hz (2160p) geeignet and 3D 50/60Hz
- uninterrupted movements (jerking) and transitions, Variable Refresh Rate (VRR)
- new HDMI standard for impeccable movies and gaming experiences
- HDCP 2.2
- supported color space RGB with 14 Bit, color subsampling YCbCr 4:2:0, Video-Compression DSC 1.2
- Data rate max. 48 Gbit/s



3.00 m	47575	Bulk
--------	-------	------



Clicktronic Casual

USB-C™/HDMI™ adapter cable

high-speed adapter from USB-C™/ HDMI™

- suitable for numerous mobile devices such as smartphones, tablets
- pure copper conductor and 2-way shielding for clear signal quality
- supports maximum SuperSpeed data transmissions up to 10 Gbps 4K@60 Hz
- 24 carat gold-plated contacts for minimum transmission resistance

1.00 m	44928	Retail Box
--------	-------	------------

2.00 m	44929	Retail Box
--------	-------	------------

3.00 m	44930	Retail Box
--------	-------	------------





Clicktronic Casual

USB-C™/DisplayPort adapter cable

high-speed adapter from USB-C™ / DisplayPort

- suitable for numerous mobile devices such as smartphones, tablets
- pure copper conductor and 3-way shielding for clear signal quality
- supports maximum SuperSpeed data transmissions up to 10 Gbps 4K@60 Hz
- 24 carat gold-plated contacts for minimum transmission resistance

1.00 m	44931	Retail Box
2.00 m	44932	Retail Box
3.00 m	44933	Retail Box





Goobay

Micro USB charger 1 A

Power supply for many devices with Micro-USB connection such as Smartphones

- allows for a quick charge directly at the socket
- voltage of 100 V - 240 V also allows for use abroad
- incl. cable management for individual cable length
- overload and short circuit protection
- charging controller for optimal performance

black 49529 Retail Polybag



Varta

CR 1/2 AA Varta (6127) 950 mAh

Lithium manganese dioxide battery, 3 V

24.9 x 14.5 mm



49712

1 pc. in blister