

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
A															A
B															B
C															C
D	Art.-Nr. / Item No. 94169 94170 94171 94172 94173 94174		Beschreibung / Description CAT 5-0025 U/UTP (1x90°) SCHWARZ 0.25m CAT 5-0050 U/UTP (1x90°) SCHWARZ 0.50m CAT 5-0100 U/UTP (1x90°) SCHWARZ 1m CAT 5-0200 U/UTP (1x90°) SCHWARZ 2m CAT 5-0300 U/UTP (1x90°) SCHWARZ 3m CAT 5-0500 U/UTP (1x90°) SCHWARZ 5m		Länge / Length (L) 250 -20/+30 mm 500 -20/+30 mm 1000 -20/+30 mm 2000 ±40 mm 3000 ±50 mm 5000 ±70 mm		Farbe / color schwarz / black		Anschlussdiagramm / Wiring diagram PIN OUT P1 P2 1 1 weiß/orange / white/orange 2 2 orange / orange 3 3 weiß/grün / white/green 6 6 grün / green 4 4 blau / blue 5 5 weiß/blau / white/blue 7 7 weiß/braun / white/brown 8 8 braun / brown				Aderquerschnitt / Wire cross section $\frac{A-A}{5:1}$ Leiter / Conductor: 7/0.15CCA Isolierung / Insulation: HD-PE Mantel / Jacket: OD 4.6 ±0.2 mm		D
E	94161 94162 94163		CAT 5-0025 U/UTP (1x90°) WEISS 0.25m CAT 5-0050 U/UTP (1x90°) WEISS 0.50m CAT 5-0100 U/UTP (1x90°) WEISS 1m		250 -20/+30 mm 500 -20/+30 mm 1000 -20/+30 mm		weiß / white						E		
F	94164 94165 94166 94167 94168		CAT 5-0200 U/UTP (1x90°) WEISS 2m CAT 5-0300 U/UTP (1x90°) WEISS 3m CAT 5-0500 U/UTP (1x90°) WEISS 5m CAT 5-1000 U/UTP (1x90°) WEISS 10m CAT 5-1500 U/UTP (1x90°) WEISS 15m		2000 ±40 mm 3000 ±50 mm 5000 ±70 mm 10000 ±100 mm 15000 ±150 mm								F		
G			CAT 5e Patchkabel 1x 90° gewinkelt, U/UTP - Slimline-Knickschutzhülle - Rastnasenschutz und Längenangabe am geraden Stecker - Paarfolge nach EIA/TIA 568B - Gigabit (10/100/1000 Mbit) Netzwerk geeignet		CAT 5e patchcable 1x 90° angled, U/UTP - slimline strain relief - latch protection and length specification on straight plug - pair-sequence acc. to EIA/TIA 568B - Gigabit (10/100/1000 Mbit) network suitable								G		
H			Anschlüsse: RJ45-Stecker 90°(8P8C), RJ45-Stecker (8P8C) Kontakte: vergoldet Material Kabelmantel: PVC Shieldungsklasse: U/UTP Innenleiter: AWG 26/7 (stranded), 4 x 2 x 7/0.15 ±0.005 CCA+PVC Spannungsfestigkeit: 300 V — Kontaktwiderstand: max. 3 Ω Isolationswiderstand: 10 MΩ @ 10 ms Impedanz: 100 Ω		Connectors: RJ45 plug 90° (8P8C), RJ45 plug (8P8C) Contacts: gold-plated Material cable jacket: PVC Shielding: U/UTP Inner conductor: AWG 26/7 (stranded), 4 x 2 x 7/0.15 ±0.005 CCA+PVC Withstanding voltage: 300 V — Contact resistance: max. 3Ω Insulation resistance: 10 MΩ @ 10 ms Impedance: 100 Ω								H		
I	Änderungen Datum Name 03.03.2025 ir 13.01.2025 fw		Datum Name 10.02.2021 aw 10.02.2021 aw		Bezeichnung CAT 5-XXXX U/UTP (1x90°) XXXX Xm Zeichnungs-Nr.: 94169ff				Blatt 1/1 von				I		
J			Änderungen vorbehalten / Subject to change										J		
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	