



Product	Name	Speaker Cable					
Conductor	Material	Copper Coated Aluminum				Electrical Characteristics (20°C)	Max. Conductor DC Resi at 20°C (Ω/M) 0.00
	Nom.O.D. (mm)	2x81/0.25 (2x4.0mm <sup>2</sup> )	Up	+0.02	Rated Voltage (V)		
			Down	-0.02			
	Jacket	External O.D.	5mm×2C	Up	+0.05	Sheath Physical Properties	Rated Temperature(°C) 70°C
			Down	-0.05			
	Surface	Smooth		View			
	Material	PVC(complies RoHS Reach) CPR(Eca)		Drawn By			
				Page			

no.	Packaging	Length (m)	color
67726	Cable coil	10	transparent
67727	Cable coil	25	transparent
67729	Cable coil	50	transparent
15021	Cable Reel	100	transparent
67741	Cable coil	10	white
67742	Cable coil	25	white
67743	Cable coil	50	white
15138	Cable Reel	100	white
67738	Cable coil	10	red/black
67739	Cable coil	25	red/black
67740	Cable coil	50	red/black
15025	Cable Reel	100	red/black

Eca Fire class (CPR) according to DIN EN 13501-6

Änderungen			Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	12.08.2021	TL	LSK 2x4,0mm <sup>2</sup>	1/1
12.08.2021	TL	gepr.:				
		Norm:			Zeichnungs-Nr.: 15138 15021 15025 67743 67729 67740 67742 67727 67739 67741 67726 67738	von
Änderungen vorbehalten / Subject to change						

